

WD9300

2D Desktop Barcode Scanner



Features

- Plug and play, No need to install any software and drivers.
- Ideal work for Windows XP/10/8/7, Mac OS, Linux.
- 1800 times/ second, ultra-fast decoding speed and high accuracy.
- Made of high quality material, durable and not easy to damage.
- Can easily capture bar codes 1D, 2D/QR on labels, paper, and mobile phone or computer displays. no need to hold the scanner, release your hands.
- Handsfree barcode scanner improve your efficiency with infrared auto-sensing sensor.
- Can directly fixe it onto your desk or table, no need to pick up the scanner when scanning, improving working efficiency, save your time.
- Application fields: retail shop, clothing store, supermarket, library, book store, pharmacy store, warehouse, parking system etc.



Specifications

| Scanner parameters : | |
|------------------------|---|
| Optical resolution | CMOS 640 pixels (H) x 480 pixels (V) |
| Lighting source | red LED supplement |
| Resolution | ≥4mil |
| Scanning speed | 1800 times/s |
| Scanning angle | Roll 360° / Pitch ±65°/ Yaw ±65° |
| Field of View | 39°(H) X 29°(V) |
| Sweeping barcode type | paper, thin film medium one-dimensional; mobile phone, flat screen, etc. |
| Printing contrast | 20% |
| Error rate | ≤1/2,000,000 |
| Interface type | USB |
| Prompt mode | Buzzer, LED |
| Decoding Capability | 1D: Codabar, Code 39, Code 32 Pharmaceutical (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS128-1, UPC-A, UPC-E, EAN/JAN8-, EAN/JAN13-, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, China Post(Hong Kong 2 of 5), Korea Post. |
| | 2D: PDF417, Micro PDF417, GS1 Composite Codes, QR Code, Data Matrix, MaxiCode, Aztec, HANXIN, DOT Code, Codeblock, etc. |
| Electric voltage | 5V DC |
| Current | Work Current 320mA, Stand-by Current 235mA, Starting Current 315mA |
| Ambient Light Immunity | 0-100,000 Lux |



WDLINK

Mechanical parameters

| | |
|------------|---------------------------|
| Dimensions | 140.20mm x 84mm x 90.10mm |
|------------|---------------------------|

| | |
|--------|------|
| Weight | 249g |
|--------|------|

Enviromental parameter

| | |
|---------------------|------------|
| Working temperature | -20°C~60°C |
|---------------------|------------|

| | |
|---------------------|------------|
| Storage temperature | -30°C~70°C |
|---------------------|------------|

| | |
|----------|---|
| Humidity | 5% to 95% relative hum idity,non-condensing |
|----------|---|

| | |
|-----------|----|
| Drop test | 2m |
|-----------|----|



WDLINK