

WD3000VA

Single Phase 1600W 3000VA Low Frequency offline UPS Sine Wave
UPS Uninterrupted Power Supply Built-in Battery UPS



Features

- Simple, compact and generous machine appearance
- Super wide mains input range
- Excellent microprocessor to ensure reliable operation
- Automatic adjustment of the AC mains power boost, step-down, stable voltage output
- Mains restart function
- Output modified sine wave
- Automatic charge in off-mode
- Cold start function
- Compatible generators

Application

- PC/Fax/Modem
- Small server/Lan
- Cash-counting



- Attendance machine
- Miniature Terminal Equipment
- SOHO Equipment

Specifications

Line Interactive UPS	
Model :	WD3000VA
Capacity :	3000VA/1600W
Input	
Voltage :	220VAC
AC Mains Input Voltage Range :	145-280 VAC (same as AC mains)
Frequency :	50 Hz/60Hz
Output	
Voltage Range :	±10%
Frequency Range :	50 Hz ±1 Hz(adaptive)
Transfer Time :	2-6ms,<10ms
Waveform :	Pure sine wave
Battery	
Battery Type & Quantity :	12 V7Ahx4
Battery Charging Time	4 hours charge to 90%
LED Indicators	
AC Mode :	Green light
Battery Mode :	Red light flash
Audible Alarm	
Battery Mode :	Alarm beeps every six seconds
Low Battery :	Alarm beeps every second



WDLINK

Overload :	Alarm beeps twice every second
Fault	Alarm beeps continuously
Protection Function	
Comprehensive Protection :	Overload, deep discharge and over-charge protection
Environment	
Temperature And Humidity :	Relative humidity 0-90% and temperature 0 -40°C (No-condensing)
Noise :	less than 40dB at one meter distance
Physical Function	
Dimensions D X W X H (mm) :	405x144x213
Net Weight (kgs) :	17.6



WDLink