

# WD650VA

Single Phase 360W 650VA Low Frequency Offline UPS Sine Wave  
UPS Uninterrupted Power Supply Built-in Battery UPS



## Features

- Simple, compact and generous machine appearance
- Super wide mains input range
- Excellent microprocessor to ensure reliable operation
- Automatic adjustment of the AC mains power boost, step-down, stable voltage output
- Mains restart function
- Output modified sine wave
- Automatic charge in off-mode
- Cold start function
- Compatible generators

## Application

- PC/Fax/Modem
- Small server/Lan
- Cash-counting



- Attendance machine
- Miniature Terminal Equipment
- SOHO Equipment

## Specifications

Line Interactive UPS	
Model :	WD650VA
Capacity :	650VA /360W
Input	
Voltage :	220VAC
AC Mains Input Voltage Range :	145-280 VAC (same as AC mains)
Frequency :	50 Hz/60Hz
Output	
Voltage Range :	±10%
Frequency Range :	50 Hz ±1 Hz(adaptive)
Transfer Time :	2-6ms,<10ms
Waveform :	Modified sine wave
Battery	
Battery Type & Quantity :	12V7.2Ah x1
Battery Charging Tiime	6 hours charge to 90%
LED Indicators	
AC Mode :	Green light
Battery Mode :	Red light flash
Audible Alarm	
Battery Mode :	Alarm beeps every six seconds
Low Battery :	Alarm beeps every second



WDLINK

Overload :	Alarm beeps twice every second
Fault	Alarm beeps continuously
<b>Protection Function</b>	
Comprehensive Protection :	Overload, deep discharge and over-charge protection
<b>Environment</b>	
Temperature And Humidity :	Relative humidity %90-0 and temperature °40 -0C (No-condensing)
Noise :	less than 40dB at one meter distance
<b>Physical Function</b>	
Dimensions D X W X H (mm) :	335x87x143
Net Weight (kgs) :	4.4



WDLink