

WD9000

2D Wireless Barcode Scanner



Features

- Factory direct sale, Low price high performance.
- With mini USB receiver, plug and play.
- Support reading bar codes from screen.
- Powerful decode ability, fast scanning 1D/2D barcodes.
- Large capacity battery, 1800MAH Li-ion battery.
- 2.4GHz wireless and USB wired connection, 2 modes for option.
- Supports Handheld / Continuous / Auto-Induction , 3 modes for option.
- 2.4G Wireless communication distance outdoor 100m, indoor 80m.
- Support connection with computer, laptop. Compatible Operating System for Linux, Windows XP, 7, 8, 10.
- Application fields: Supermarket, Retail, Warehouse, Logistic, Library, Medical etc.
- Can be customized according to customer demand.



Specifications

Scanner parameters :

Transmission mode :	2.4G wireless/wired
Storage :	10000 barcodes
Distance :	100m/1.5m
CPU :	ARM -32bit Cortex
Sensor :	640*480 CMOS
Interface :	USB, USB-COM
Resolution :	4mil
Light aimer :	617nm LED
Battery :	1800mAh
Indication :	Buzzer & LED
Decoding speed :	500scans/sec
Illumination :	6500K LEDs
Button life :	5000,000 times
Printing Contract :	≥25%

Trigger Mode : Handheld,Continuous,Auto-Induction

250Lux Depth of Field	13mil-EAN13	50-240mm
	4mil-code39	50-90mm
	20mil-QR	40-280mm
	10mil-PDF417	40-250mm

Decode Capability :

1D :	UPC-A, UPC-E, EAN8-, EAN13-, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5, Coda bar, MSI Plessey, RSS, etc.
2D :	QR Code, Data Matrix, PDF417, Aztec code, Maxicode, etc.



WDLINK

Trigger Mode :	Handheld,Continuous,Auto-Induction
Scanning angle :	Angle of rotation 360°, inclination± 65°, declination ± 60°
Working Temperature :	-20°C ~ -50°C
Working current :	38mA-185mA(max peak)
Working time :	3 to 7days
Anti inference :	0-100000Lux Max
Certificate :	CE, FCC, RoHS, IP54
Storage Temperature :	-40°C ~ -60°C
Standby current :	30mA
Charging power :	5V
Relative Humidity :	0 ~ 95%
Drop test :	2m

Product Pictures



WDLink