

WD8230

4inch Thermal Transfer Printer



USB



WIFI



BT



LAN



Features

- Double Printer Mode: Thermal transfer and Direct thermal.
- 32-bit High -efficiency CPU
- Detachable printer rubber rollers and print heads
- Shipping label printer supports USB/ USB+LAN/USB+Bluetooth/USB+WIFI
- 8MB Flash memory, 8MB SDRAM,High quality print head, 203DPI resolution
- The label printer with 127m/s high speed, low noise and clear printing.
- Suitable for thermal direct labels from 115-25.4mm, support continuous paper, label paper, folding paper, tag paper.
- Support computer of Windows 10/8/7/XP Mac OS with USB port, compatible with Android/iOS/Windows.
- Wide application: Major selling/shipping platforms including Amazon, eBay , Paypal, Shopify, Etsy , Poshmark, Shippo, Shipstation, UPS, DHL, Fedex, Supermarket, Retail store, Clothing store, Post package industry, Medical industry, Home, Office and more.



Specifications

Printing Features :

Resolution :	203 DPI(300 DPI Optional)
Printing method :	Thermal Transfer / Direct Thermal
Max.print speed :	127 mm / s
Interface :	USB / USB+Lan / USB+WIFI / USB+ Bluetooth
Max.print width :	108 mm
Max.print length :	1778 mm
Media type :	Continuous, gap, black mark, fan-fold and punched hole
Media width :	25.4 mm ~ 115 mm
Media thickness :	0.06~0.18 mm
Media core diameter :	25.4 ~ 76.2 mm
Label length :	10 mm ~1778 mm
Ribbon Length :	100m, Max OD (External Diameter)35mm
Print head life :	30 km
Driver :	Windows/ Linux/ Mac
SDK :	Windows/ Android/ iOS

Performance Features

Processor :	32-bit CPU
Memory :	8MB Flash Memory, 8MB SDRAM
Sensors :	Gap sensor; Cover opening sensor; Black mark sensor

Fonts/Graphics/Symbologies/Physical Features

Internal fonts :	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
------------------	---



WDLINK

1D bar code :	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC (5)2 digits add-on, MSI, PLESSEY, POSTNET, China POST,GS1 DataBar, Code 11
2D bar code :	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Rotation :	0°, 90°, 180°, 270°
Emulaion :	TSPL, EPL, ZPL, DPL
Dimension :	246 mm (D) x 199 mm (W) x 168 mm (H)
Weight :	1.6 kg

Environmental Conditions & Power supply

Operation environment :	5 ~ 40°C (41~104°F) , Humidity: 25 ~ %85 no condensing
Storage environment :	-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ %90 no condensing
Input :	AC 110-240V,18A , 50-60Hz
Output :	DC 24V 2.5A 60W

Product Pictures



WDLink