

# WD9700

## 2D Wireless Barcode Scanner



### Features

- High decoding ability and high performance.
- Large capacity battery, 2600MAH Li-ion battery.
- Super memory function, can store up to 300,000 barcodes.
- Super pairing function, support one to one, one to many, many to one.
- Supports 1D/2D bar-codes on paper/screen.
- Base function as receiver and charger, free of charging trouble.
- Super transmission distance, 500m effective open distance (200-50m indoor distance).
- Application fields: Supermarket, Retail, Warehouse, Logistic, Library, Medical etc.
- The head of the scanner, the handle and the base are protected by rubber, Antiknock, full quakeproof design, withstand 3m drops.
- Can be customized according to customer demand.



# Specifications

## Scanner parameters :

Transmission mode :	433M wireless
Storage :	300,000 barcodes
Distance :	500m
Sensor :	640*480 CMOS
CPU :	ARM -32bit Cortex
Battery :	3.7V-2600mAh
Indication :	Buzzer & LED
Light aimer :	617nm LED
Resolution :	4mil
Interface :	USB
Decoding speed :	500scans/sec
Illumination :	6500K LEDs
Button life :	8000,000 times
Material :	ABS+Rubber

## Trigger Mode : Handheld,Continuous,Auto-Induction

250Lux Depth of Field :	13mil-EAN13	60-290mm
	4mil-code39	30-150mm
	15mil-QR	20-300mm
	15mil-PDF417	40-300mm

## Decode Capability :

1D :	UPC-A, UPC-E, EAN8-, EAN13-, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5, Coda bar, MSI Plessey, RSS, etc.
2D :	QR Code, Data Matrix, PDF417, Aztec code, Maxicode, etc.



WDLINK

Trigger Mode :	Handheld,Continuous,Auto-Induction
Scanning angle :	Angle of rotation 360°, inclination± 65°, declination ± 60°
Temperature storage :	-40°C ~ -60°C
Working time :	3 to 10 days
Anti inference :	0- 100000Lux Max
Certificate :	CE, FCC, RoHS, IP54
Temperature working :	-20°C to -60°C
Relative Humidity :	0 ~ 95%
Printing Contract :	≥25%
Drop test :	3m

## Product Pictures



WDLink